

Material Safety Data Sheet



Section 1 Company and Product Identification


L. Robinson & Company (Gillingham) Limited, Incorporating Jubilee® Clips Limited Owens Way, Gads Hill, Gillingham, Kent, ME7 2RS, UK

Tel: +44 (0)1634 281200 Fax: +44 (0)1634 280101

Email: sales@jubileeclips.co.uk
http://www.jubileeclips.co.uk

Jubilee® Original 304 Stainless Steel (W4) Range,

manufactured to BS5315:1991



Part	BS	-	ment (X)	Band Width (W)	Band Thickness (T)	(Z)	(Y)	Recommended Torque	Max Torque	Recommended Max Pressure
Number	No	mm	Inches	mm	mm	mm	mm	Nm	Nm	PSI
000SS	12	9.5- 12	3/8 - 1/2	9.9	0.762	20.5	12.5	3.4	4.5	203
M00SS	16	11- 16	1/2 - 5/8	9.9	0.762	20.5	12.5	3.4	4.5	203
00SS	20	13- 20	1/2 -3/4	9.9	0.762	20.5	12.5	3.4	4.5	203
OSS	22	16- 22	5⁄8 - 7∕8	13	0.914	24.5	16	4.2	5.6	203
OXSS	25	18- 25	34 - 1	13	0.914	24.5	16	4.2	5.6	203
1ASS	30	22- 30	⅓ - 1⅓	13	0.914	24.5	16	5.1	6.8	203
1SS	35	25- 35	1 - 13/8	13	0.914	24.5	16	5.1	6.8	102
1XSS	40	30- 40	1% - 1%	13	0.914	29	16	5.1	6.8	102
1MSS	45	32- 45	1¼ - 1¾	13	0.914	29	16	5.1	6.8	102
2ASS	50	35- 50	1% - 2	13	0.914	29	16	5.9	7.9	102
2SS	55	40- 55	1% - 2%	13	0.914	33	16	5.9	7.9	102
2XSS	60	45- 60	1¾ - 2¾	13	0.914	33	16	5.9	7.9	102
3SS	70	55- 70	21/8 - 23/4	13	0.914	33	16	6.7	9	102
3XSS	80	60- 80	2% - 3%	13	0.914	33	16	6.7	9	44
4SS	90	70- 90	2¾ - 3½	13	0.914	33	16	6.7	9	44
4XSS	100	85-100	3¼ - 4	13	0.914	33	16	6.7	9	44
5SS	120	90-120	3½ - 4¾	13	0.914	33	16	6.7	9	44
6SS	140	110-140	4% - 5½	13	0.914	33	16	6.7	9	44
6XSS	150	120-150	4¾ - 5%	13	0.914	33	16	6.7	9	18
7SS	165	135-165	5¼ - 6½	13	0.914	33	16	5.9	7.9	18
7.5SS	190	158-190	6¼ - 7½	13	0.914	33	16	5.9	7.9	18
8.5SS	216	184-216	7¼ - 8½	13	0.914	33	16	5.9	7.9	18
9.5SS	242	210-242	8¼ - 9½	13	0.914	33	16	5.9	7.9	18
10.5SS	267	235-267	9¼ - 10½	13	0.914	33	16	5.9	7.9	18
11.5SS	292	260-292	10¼ - 11½	13	0.914	33	16	5.9	7.9	18
12.5SS	318	286-318	11¼ - 12½	13	0.914	33	16	5.9	7.9	18

Section 2 Composition/Information on Ingredients

Composition/Information on constituents of iron alloy.

Manganese < 11% Chromium < 30% Nickel < 38% Mo < 8 %

Other elements vary such as Si, Cu, Ti, in each alloy composition and are generally not classified as hazardous, or are below the concentration levels for classification of these alloys as hazardous, and are not subject to recognised exposure limits.

Section 3 First Aid Measures

Inhalation: There are no specific symptoms associated with steel in the product forms. Skin: There are no specific symptoms associated with steel in the product forms.

Eyes: Not applicable. Ingestion: Not applicable.

Section 4 Fire Fighting Measures

Non flammable

Section 5 Handling and Storage

Store in a dry area

Section 6 Physical and Chemical Properties

Colour: Metallic grey/silver

Odour: None Form/state: Solid 1454 °C Melting point: 870°C Max service temp: -196 °C Min service temp: Magnetism: 1.008μ Resistance: 72 μΩ Density: 8.03 g/cm³

Section 7 Stability and Reactivity

Stability: Stable in normal condition

Reacts with: Reacts with strong acids, and hydrogen is then one of the substances emitted.

Corrosion Resistance: NSS 1000hours

Section 8 Toxicological Information

Nickel is classified as a skin sensitizer however numerous patch tests have established that most stainless steels do not cause sensitization, but a few types may result in allergic skin reactions in sensitized individuals after prolonged contact.

No carcinogenic effects resulting from exposure to stainless steels have been reported, either in epidemiological studies or in tests with animals.

Section 9 Ecological Information

No ecological effects are known for the product as a whole.

Section 10 Disposal Considerations

Disposal method: Recyclable, Jubilee® clips' Original 304 Stainless Steel Range are made from key raw

material for the production of new Stainless steel. Steel is the world's most recycled

construction material and can be recycled with retained material properties.

Section 11 Transport Information

No special requirements are necessary in transporting these products.

Section 12 Regulatory Information

This product conforms to EU Regulation 1097/2006 (REACH)
This product is compliant with EU directive 2011/65/EU (ROHS2)
BS EN ISO 9001:2008 FM00547
BS EN ISO 14001:2004 EMS573195
BS OHSAS 18001:2007 OHS601983
Manufactured to BS5315:1991
Lloyds Register Type Approval Certificate number 96/00006(E2)

Quality Assurance:







Section 13 Other Information

The information above is believed to be accurate and represents the best information currently available to L. Robinson & Co Ltd. However, L. Robinson & Co Ltd make no warranty of merchantability or any other warranty, expressed or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall L. Robinson & Co Ltd be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if L. Robinson & Co Ltd has been advised of the possibility of such damages.

Document Issue Date: 18th April 2019

Revision Number: 14